

30.00R51 HA168



Characters:

- 1.The huge tread blocks give tyre better traction and cut resistance.
- 2.The wide horizontal groove improves heat dispersion and self cleaning.
- 3.The full support design of tyre shoulder ensures the minimum crown deformation.



Technical Data

Tire Size	Unit	Dimensions of New Tire(mm)						Dimensions of In-service Tire					Rim		TKPH
		Tread Depth	Overall Section Width	Section Height	External Tire Diameter	Rolling Circumference	Inter capacity (L)	Maximum Overall Section Width	Maximum External Diameter	Static Loaded Radius	Static Loaded Section Width	Minimum Dual Spacing	Standard	Optional	Average
30.00R51	mm	75	845	795	2878	8105	2453	915	3035	1290	990	1005	22.00/4.5		588
	inches	2.95	33.27	31.30	113.31	319.09		36.02	119.49	50.79	38.98	39.57			

Payload Limit Under Different Air Pressure

30.00R51	Air Pressure	kPa	450	475	500	525	550	575	600	625	650
		psi	65	69	73	76	80	83	87	91	94
Payload Limit	kg	25750	26500	28000	29000	30000	30750	31500	32500	33500**	
	lbs.	56800	58400	61500	64000	66000	68000	69500	71500	74000**	

- Note : 1.The number in boldface means the HIGHEST payload of it's star class in the same cell.
 2.When highest speed is 65 km/h, the payload should decrease 12% with the same pressure.

