



53/80R63 HA688



Characters:

- 1.Brand-new pattern design make it own excellent self-cleaning ability.
- 2.The large tread blocks help tyre owns better road traction and cut resistance.
- 3.Perfect running capability.
- 4.Suitable for different mine and road condition.



Technical Data

Tire Size	Unit	Dimensions of New Tire(mm)						Dimensions of In-service Tire					Rim		TKPH
		Tread Depth	Overall Section Width	Section Height	External Tire Diameter	Rolling Circumference	Inter capacity (L)	Maximum Overall Section Width	Maximum External Diameter	Static Loaded Radius	Static Loaded Section Width	Minimum Dual Spacing	Standard	Optional	Average
53/80R63	mm	85	1330	1094	3780	10298		1480	3845	1639	1625	1678	36.00/5.0	38.00/5.0	1277
	inches	3.35	52.36	43.07	148.82	405.43	7850	58.27	151.38	64.53	63.98	66.06			

Payload Limit Under Different Air Pressure

53/80R63	Air Pressure	kPa	450	475	500	525	550	575	600
		psi	65	69	73	76	80	83	87
	Payload Limit	kg	67000	69000	71000	75000	77500	80000	82500**
		lbs.	147500	152000	156500	165500	171000	176500	182000**

Note: 1.The number in boldface means the HIGHEST payload of it's star class in the same cell.

2.When highest speed is 65 km/h, the payload should decrease 12% with the same pressure.

