



53/80R63 HA710



Characters:

1. Equal block design makes the tire wear more even.
2. The connected horizontal grooves ensure excellent performance for drainage and self-cleaning.
3. Perfect ability for running traction.
4. Suitable for different mine and road condition.



Technical Data

Tire Size	Unit	Dimensions of New Tire(mm)						Dimensions of In-service Tire					Rim		TKPH
		Tread Depth	Overall Section Width	Section Height	External Tire Diameter	Rolling Circumference	Inter capacity (L)	Maximum Overall Section Width	Maximum External Diameter	Static Loaded Radius	Static Loaded Section Width	Minimum Dual Spacing	Standard	Optional	Average
53/80R63	mm	97	1400	1124	3845	10453	8320	1437	3845	1653	1615	1752	36.00/5.0	38.00/5.0	1580
	inches	3.82	55.12	44.25	151.38	411.54		56.57	151.38	65.08	63.58	68.98			

Payload Limit Under Different Air Pressure

53/80R63	Air Pressure	kPa	450	475	500	525	550	575	600
		psi	65	69	73	76	80	83	87
	Payload Limit	kg	67000	69000	71000	75000	77500	80000	82500**
		lbs.	147500	152000	156500	165500	171000	176500	182000**

Note : 1.The number in boldface means the HIGHEST payload of it's star class in the same cell.

2.When highest speed is 65 km/h, the payload should decrease 12% with the same pressure.

