



14.00R25 HA710



Characters:

- 1.The design of equal block leads to a more even wear;
- 2.The connected horizontal grooves ensure excellent performance for drainage and self-cleaning;
- 3.Perfect running traction and pass ability;
- 4.Greater load capability, applicable to different mine types and road condition.



Technical Data

Tire Size	Star Rating	TRA Code	Unit	Dimensions of New Tire			Dimensions of In-service Tire			Rim		TKPH
				Tread Depth	Overall Section Width	External Tire Diameter	Static Loaded Radius	Static Loaded Section Width	Minimum Dual Spacing	Standard	Optional	
14.00R25	★★★	E-4	mm inches	36 1.42	385 15.16	1415 55.71	652 25.67	430 16.93	456 17.95	10.00/2.0	10.00/1.5	104

Payload Limit Under Different Air Pressure

14.00R25	Air Pressure	kPa	700	725	750	775	800	825	850	875	900	925	950
		psi	102	105	109	112	116	120	123	127	131	134	138
	Payload Limit	kg	5800	6220	6640	7060	7480	7900	8320	8740	9160	9580	10000**
		lbs.	12800	13700	14600	15600	16500	17400	18300	19300	20200	21100	22000**

Note : 1.The number in boldface means the HIGHEST payload of it's star class in the same cell.
 2.When highest speed is 65 km/h, the payload should decrease 12% with the same pressure.

