



59/80R63 HA710



Characters:

- 1.The new pattern HA710 has better self-cleaning ability;
- 2.The larger tread blocks help the tire with better traction and cut resistance;
3. Great pass ability;
- 4.Applicable to various types of mining condition.



Technical Data

Tire Size	Unit	Dimensions of New Tire(mm)						Dimensions of In-service Tire					Rim		TKPH
		Tread Depth	Overall Section Width	Section Height	External Tire Diameter	Rolling Circumference	Inter capacity (L)	Maximum Overall Section Width	Maximum External Diameter	Static Loaded Radius	Static Loaded Section Width	Minimum Dual Spacing	Standard	Optional	
59/80R63	mm inches	105 4.13	1480 58.27	1217 47.91	4026 158.50	10840 426.77	9660	1650 64.96	4145 163.19	1725 67.91	1795 70.67	1860 73.23	44.00/5.0		1722

Payload Limit Under Different Air Pressure

59/80R63	Air Pressure	kPa	450	475	500	525	550	575	600
		psi	65	69	73	76	80	83	87
	Payload Limit	kg	80000	82500	87500	90000	92500	95000	100000**
		lbs.	176500	182000	193000	198500	204000	209500	220500**

Note : 1.The number in boldface means the HIGHEST payload of it's star class in the same cell.

2.When highest speed is 65 km/h, the payload should decrease 12% with the same pressure.

